

BEEM SQ 150 recessed downlighter offers powerful LED illumination in a 150mm x 150mm luminaire size. BEEM SQ 150 is available in various lumen outputs and colour temperatures with easy install spring design for simple installation BEEM offers energy efficient lighting with carbon reduction to all environments, including office space, accent and perimeter lighting, reception, breakout, amenity and circulation spaces.


Product	BEEM SQ 150	BEEM SQ 150			
Lumen Options	1100lm 3000K/4000K LED			2000lm 3000K/4000K LED	
Control	ND Non dimming	HA Analogue dimming		HD DALI dimming	
	HS Switch dimming			HX DSI dimming	
Diffuser	ET Polar frost				
Finish	WH RAL9010			Other finishes available	
Emergency Options	E3 3 hour integrated self contained conversion kit with green LED indicator	EA Self test emergency		EC Central battery emergency	
	ED DALI emergency			EE Emergency via independent ELED	
Technical Details	Recessed into false ceiling		Side arm retaining springs		
	CRI>80	LED Efficacy 146 lm/W - 50.000hrs		IP Rating IP20	


Please contact our technical department for the most up-to-date information on LED modules

To Specify: 150mm x 150mm downlight to suit 2000lumen cool white LED, DALI digital dimming control gear. Catalogue No BEEMSQ1502K4KHDWH

- Range of lumen outputs
- Colour tolerance MacAdam ≥ 3 •
- Homogeneous light
- Highly efficient reflector
- RAL colour to suit
- Tool-less installation

- Emergency conversions available
- Links with lighting control systems & power over ethernet
- Part L & Enhanced Capital Allowance
- Low and easy maintenance
- Long life 50,000hrs
- Zhaga replaceable LED module









Minimum Recessed Depth 86mm

LED

Nominal Size 150mm x 150mm

Cutout 135mm x 135mm

Part L2

ECA



DOWNLIGHT/ACCENT