



HUB



- Range of lumen outputs
- Homogeneous light
- Independent emergency
- Links with lighting control systems & power over ethernet
- Part L & Enhanced Capital Allowance
- Low and easy maintenance
- Replaceable LED module
- Long life 50,000hrs

Product	HUB			
Lumen Options	7000lm 4000K/3000K	8000lm 4000K/3000K	9000lm 4000K/3000K	
Control	ND Non dimming	HA Analogue dimming	HX DSI dimming	HD DALI dimming
Diffuser Option	ET Polar frost			
Uplight Option	UL Uplight			
Luminaire Size	S1RD Ø600mm	S2RD Ø900mm	S3RD Ø1000mm	S4RD Ø1200mm
	S1SQ 600mm x 600mm	S2SQ 900mm x 900mm	S3SQ 1000mm x 1000mm	S4SQ 1200mm x 1200mm
Options	Please contact us to discuss size & colour options. Standard depth 300mm. Other depths are available			
Emergency Option	EE Emergency via independent ELED		EC Central Battery Emergency	
Technical details	Suspended from ceiling rose			
	CRI>80	LED Efficacy 168 lm/W 50.000hrs	IP Rating IP20	
Please contact our technical department for the most up-to-date information on LED modules				
To Specify: Ø1000mm x 200mm depth luminaire with 3000K LED, non dimming driver and RAL3000 colour fabric. Catalogue No HUB783KHDETWSS2RD(COLOUR)				

This eclectic group of pendants can be produced in a wide range of sizes and styles. A wide range of colours can be supplied. The HUB is elegantly designed to incorporate LED downlight with optional uplight. These drum style pendants are specifically designed for the workplace environment ensuring energy savings and function does not compromise flair.



LED

Standard Depth
200mm

Various Diameters
Available

Various Colours
Available

Part L2
✓

ECA
✓

BUILT
IN
BRITAIN



futuredesigns.co.uk

LIGHT5K4KNDETE3
HOW TO SPECIFY

- Luminaire
- Lumen Output
- LED Colour
- Driver
- Options
- Emergency

FUTURE
DESIGNS