



# SKYLINE



SKYLINE is impressive as it is practical. This super system was designed to not just illuminate but house all modern cable systems and incorporate systems such as downlighter modules, PIR and voice evacuation systems. Its unique engineered design includes specially crafted junction sections, which ensure LV and ELV cables do not cross. Engineered modules allow for seamless joins and flexibility in the design. SKYLINE can be designed to follow staircase structures and architectural details as well as providing excellent lighting to the working environment.

- Designed to incorporate light as well as being a discrete trunking system
- Bespoke luminaire which can house speakers, smoke detectors and daylight sensors
- Totally unique lighting product
- Range of lumen outputs
- Homogeneous light
- Suspended design
- Integrated emergency
- Links with lighting control systems & power over ethernet
- Part L & Enhanced Capital Allowance
- Low and easy maintenance
- Replaceable LED module
- Long life 50,000hrs

Product	SKYLINE			
Lumen Options (1200mmx300mm) Nominal dimension	4000lm 4000K LED	5000lm 4000K LED	6000lm 4000K LED	6900lm 4000K LED
	3900lm 3000K LED	4900lm 3000K LED	5800lm 3000K LED	6600lm 3000K LED
Lumen Options (1500mmx300mm) Nominal dimension	5000lm 4000K LED	6300lm 4000K LED	7500lm 4000K LED	8600lm 4000K LED
	4900lm 3000K LED	6100lm 3000K LED	7300lm 3000K LED	8300lm 3000K LED
Control	ND Non dimming	HA Analogue dimming		HD DALI dimming
	HS Switch dimming		HX DSI dimming	
Diffuser Option	ET Polar frost Diffuser		FMP Microprism	
Options	X16 Power Over Ethernet	CW Cableway		DL Downlight module
	PIR Presence detector	SD Smoke detector		JN Junction modules
Emergency Options	E3 3 hour integrated self contained conversion kit with green LED indicator	EA Self test emergency		EC Central battery Emergency
	ED DALI emergency		EE Emergency via ELED	
Technical Details	WS Suspended via wire suspensions			
	CRI>80	LED Efficacy 169 lm/W 50.000hrs		IP Rating IP20
Please contact our technical department for the most up-to-date information on LED modules				
To Specify: 1200mm x 300mm luminaire to suit 5000lumen cool white LED, DALI digital dimming control gear and polar frost diffuser. Catalogue No SKYLINE5K4KHDETW5				



LED	Depth 125mm	Nominal Width 400mm	Nominal Length 900mm to 1500mm
-----	----------------	---------------------------	---



BUILT  
IN  
BRITAIN



[futuresdesigns.co.uk](http://futuresdesigns.co.uk)

LIGHT5K4KNDETE3  
HOW TO SPECIFY  
Luminaire  
Lumen Output  
LED Colour  
Driver  
Options  
Emergency

FUTURE  
DESIGNS